

TRITURADOR INDUSTRIAL

Trituradores con una sola etapa de molienda con efecto de bombeo.


- Mueble construido en acero inoxidable AISI 304 con patas de anclaje.
- Los desechos no solamente están molidos, sino que también dispersos en el agua y expulsados a presión de la misma forma que una bomba centrífuga.
- Se trata de modelos entre los más económicos de su categoría, sus características hacen un verdadero molino para desechos orgánicos alimenticios.
- La molienda se efectúa mediante martillos en acero especial tratado.
- Una retención hidráulica por juntas estancas dobles evita la filtración de agua en el bloque motor.
- Equipado con protector térmico (motor) y pulsador de emergencia paro / motor.

GARBAGE DISPOSAL

Food-waste disposers with pumping effect.

- Cabinet built in AISI 304 stainless steel with fastening legs.
- Wastes are not only ground and dispersed in the water but also strongly pumped out.
- Even though it is one of the most economical machines in the field, its characteristics make it a real must for waste food disposal.
- Special steel hammer to make the grinding.
- The double ring seal makes the motor watertight.
- Equipped with thermal protection (motor) and emergency push button on / off.

MODELOS · MODELS 1,5 CV – 5,5 CV



Mod.: 4 CV

TRITURADOR INDUSTRIAL	GARBAGE DISPOSAL	1,5 CV	2 CV	3 CV	4 CV	5,5 CV
Capacidad (kg)	Capacity (kg)	150	250	350	450	550
Velocidad (r.p.m.)	Speed (r.p.m.)	1450	1450	1450	1450	1450
Ø Desagüe	Ø Drainage	75/81	75/81	75/81	75/81	75/81
Acometida de agua	Water inlet	3/8"	3/8"	3/8"	1/2"	1/2"
Consumo de agua (L/h)	Water consumption (L/h)	100	100	100	100	125
Potencia (W)	Power (W)	1100	1500	2200	3000	4000
Tensión (V - ph)	Voltage (V - ph)	230/400/440 - III				
Peso Neto (kg)	Net Weight (kg)	60	95	130	150	160